

IN THE CLAIMS:

1. (Previously Presented) A method for wireless communication between an
5 integrated circuit device and a monitoring station, said method comprising the steps of:
transmitting a wireless signal from said integrated circuit device to said
monitoring station using an antenna associated with said integrated circuit device, wherein said
antenna is a pin on said integrated circuit device, and wherein said monitoring station performs
one or more of testing, debugging and evaluating said integrated circuit.
- 10 2. (Original) The method of claim 1, wherein said antenna is incorporated in said
integrated circuit device.
3. (Cancelled)
- 15 4. (Original) The method of claim 2, wherein at antenna is printed on said integrated
circuit device.
5. (Original) The method of claim 1, wherein said signal is transmitted in
20 accordance with an 802.11 wireless standard.
6. (Original) The method of claim 1, wherein said signal is transmitted in
accordance with an ultra wide band wireless standard.
- 25 7. (Original) The method of claim 1, wherein said signal is transmitted in
accordance with a Bluetooth standard.

8. (Cancelled).

9. (Cancelled).

5 10. (Cancelled).

11. (Original) The method of claim 1, wherein said signal is a test command.

12. (Original) The method of claim 1, wherein said signal is a memory pattern to be
10 applied to a memory area on said integrated circuit device.

13. (Previously Presented) An integrated circuit device, comprising:
at least one circuit; and
an antenna for wireless communication with an external monitoring station,
15 wherein said antenna is a pin on said integrated circuit device, and wherein said monitoring
station performs one or more of testing, debugging and evaluating said integrated circuit.

14. (Original) The integrated circuit device of claim 13, wherein said antenna is
incorporated in said integrated circuit device.

20

15. (Cancelled)

16. (Original) The integrated circuit device of claim 14, wherein at antenna is printed
on said integrated circuit device.

25

17. (Original) The integrated circuit device of claim 13, wherein said signal is
transmitted in accordance with an 802.11 wireless standard.

18. (Original) The integrated circuit device of claim 13, wherein said signal is transmitted in accordance with an ultra wide band wireless standard.

5

19. (Original) The integrated circuit device of claim 13, wherein said signal is transmitted in accordance with a Bluetooth standard.

20. (Cancelled).

10

21. (Cancelled).

22. (Cancelled).

15 23. (Original) The integrated circuit device of claim 13, wherein said signal is a test command.

24. (Original) The integrated circuit device of claim 13, wherein said signal is a memory pattern to be applied to a memory area on said integrated circuit device.

20

25. (Previously Presented) A method for wireless communication between an integrated circuit device and a monitoring station, said method comprising the steps of:

transmitting a wireless signal to said monitoring station from said integrated circuit device using an antenna associated with said integrated circuit device, wherein said antenna is a pin on said integrated circuit device, and wherein said monitoring station performs one or more of testing, debugging and evaluating said integrated circuit.

25